

15W-40 SL/CI-4

Evolution Oils 15W-40 SL/CI4 is formulated with superior additives to guard against soot and varnish deposits preventing abrasive wear and oil oxidation.

Application Recommendation

The premium blend of additive technology is preferred for four stroke turbocharged and naturally aspirated diesel engines both Heavy Duty and on off road vehicles burning high and low Sulphur diesel.

Performance Features

- Premium soot and sludge handling.
- Strong diesel detergency for high level piston cleanliness and extended drain capability.
- Superior wear and bearing corrosion giving maximum engine protection.
- High Shear Stability.

Performance levels

Meets the Approvals of API CI-4/CH/CG/CF/SL/,ACEA E4/E7-12 & MB-APPROVAL 228

Typical Physical Properties

PROPERTIES	UNITS	VALUE
Density @ 20°C	g/ml	0.876
Viscosity index	none	131
Viscosity @ 40°C	cSt	115
Viscosity @ 100°C	cSt	14.7
Pour Point	°C	-39

Handling and Storage

Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Additional information-Storage

Additional information

Product contaminated rags and paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose off dirty material used to absorb safely after use.

Product Warranty

Industrial lubricants are formulated to meet or exceed industrial specifications and carries a warranty. The purchaser /end user is responsible for determining if these specifications are adequate and proper for the intended application. The warranty is limited to lubricant performance consistent with indicated specifications. No additional warranty, expressed or implied can be made.