



80W-90 GL4

Evolution Oils 80W-90 GL-4 is a Gear Lubricant that may be used in applications where API GL-4 performance is required.

Application Recommendation

Product maybe used for LCV, heavy duty trucks and buses. It can also be used in PCM vehicles where a 80w-90 API GL-4 is required.

Performance Features

- High performance EP additive system controls transmission gear tooth wear.
- Excellent load carrying capacity protects gear components against surface stress under heavily loaded conditions.
- Good thermal/oxidation stability which protects against the formation of harmful deposits and oil thickening, prolonging the life of components and lubricant.
- Ideal shear-stable formulation give improved flow properties and shiftability at low temperatures.

Performance levels

Meets the Approvals API GL-4

Typical Physical Properties

PROPERTIES	UNITS	VALUE
Density @ 20°C	g/ml	0.881
Viscosity index	none	100
Viscosity @ 40°C	cSt	157
Viscosity @ 100°C	cSt	15.5
Pour Point	°C	-33

Handling and Storage

Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Additional information-Storage

Additional information

Product contaminated rags and paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose off dirty material used to absorb safely after use.

Product Warranty

Industrial lubricants are formulated to meet or exceed industrial specifications and carries a warranty. The purchaser /end user is responsible for determining if these specifications are adequate and proper for the intended application. The warranty is limited to lubricant performance consistent with indicated specifications. No additional warranty, expressed or implied can be made.