

# 85W-140 GL5

Gear Lubricant designed to exceed the latest performance standards for heavy duty severe service.

## Application Recommendation

The correct grade gear oil recommended for many types of manual gearbox, final drives, bearings and differentials where a API GL-5 transmission oil is prescribed.

## Performance Features

- EP additives according to the phosphorus/sulphur technology.
- Anti-Friction.
- Corrosion inhibition—Prolonged gear life.
- Suitable for gear boxes, axles, transfer boxes in trucks, buses and 4WD vehicles.
- Specially recommended for highly loaded hypoid gears.

## Performance levels

Meets the Approvals API GL-5

## Typical Physical Properties

PROPERTIES	UNITS	VALUE
Density @ 20°C	g/ml	0.905
Viscosity index	none	95
Viscosity @ 40°C	cSt	360
Viscosity @ 100°C	cSt	26
Pour Point	°C	-18

## Handling and Storage

### Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

### Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Additional information-Storage

### Additional information

Product contaminated rags and paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose off dirty material used to absorb safely after use.

## Product Warranty

Industrial lubricants are formulated to meet or exceed industrial specifications and carries a warranty. The purchaser /end user is responsible for determining if these specifications are adequate and proper for the intended application. The warranty is limited to lubricant performance consistent with indicated specifications. No additional warranty, expressed or implied can be made.